

## SILICONE - 825



SILICONE 825 is a low modulus, neutral curing Silicone sealant based on a filled alkoxy curing system. Conforms to BS 5889 (A) and ISO 1160 F + G25 LM. Used for expansion joints to stone, brick, concrete and composite panels, perimeter pointing around all types of window and door frames.

Shore A	22-25	Movement Accommodation	+/-50%
Skining Time	45 mins	Elastic Recovery	85%

Code	Colour	Size	Each £	Box Qty	Box £
EBS825WH	WHITE	380ml	4.45	25	110.95
EBS825BL	BLACK	380ml	4.49	25	112.25
EBS825MG	MID GREY	380ml	4.49	25	112.25
EBS825BR	BRICK RED	380ml	4.49	25	112.25
EBS825BR	BROWN	380ml	4.49	25	112.25
EBS825BU	BUFF	380ml	4.49	25	112.25
EBS825AN	ANTHRACITE	380ml	4.49	25	112.25
EBS825MA	MAGNOLIA	380ml	4.49	25	112.25
EBS825PS	PORT. STONE	380ml	4.49	25	112.25
EBS825SA	SANDSTONE	380ml	4.49	25	112.25

## SEALANT - FIRESEAL 300 INTUMESCENT



FIRESEAL 300 is an intumescent acrylic sealant that swells when exposed to temperatures in excess of 150°C to prevent the passage of fire and smoke and has a fire rating of up to 5 hours Fire rated to BS 476 part 20. Typically used for sealing joints, voids and irregular holes in fire walls, partitions and other structures. For internal perimeter pointing of fire rated door and window frames.

Movement Accommodation	+/-20%	Skining Time	15 mins
Elastic Recovery	80%	Elongation at Break	200%

Code	Colour	Size	Each £	Box Qty	Box £
EBFS300WH	WHITE	380ml	6.85	25	154.25
EBFS300GR	GREY	380ml	6.85	25	154.25
EBFS300WHF	WHITE	600ml FOIL	9.95	12	107.46
EBFS300GRF	GREY	600ml FOIL	9.95	12	107.46

## SEALANT - FIRESEAL 400



FIRESEAL 400 is a neutral cure, elastic silicone sealant which conforms to BS476 Part 20 for fire retardancy and has a fire rating of up to 4 hours. Typically used for all building and glazing joints which require a fire rating, sealing joints, voids and irregular holes in fire walls, partitions and other structures.

Movement Accommodation	+/-50%	Skining Time	45 mins
Elastic Recovery	85%	Elongation at Break	400%

Code	Colour	Size	Each £	Box Qty	Box £
EBFS400WH	WHITE	380ml	8.49	25	189.95
EBFS400GR	GREY	380ml	8.49	25	189.95

## SILICONE - S50



Silicone S50 is a mid modulus acetox curing silicone sealant that contains a powerful anti-fungal compound to prevent mould and fungal growth in areas of high humidity. The mid modulus nature of this formulation gives improved adhesion and flexibility when compared to standard high modulus sanitary grades. Conforms to BS5889(A) and ISO 11600 G25LM.

Movement Accommodation	+/-25%	Skining Time	15 mins @ 20°C
Cure Time	3-4 mm per 24hrs	Service Temp	-40 to +150°C

Code	Colour	Size	Each £	Box Qty	Box £
EBSS50WH	WHITE	310ml	3.35	25	75.39

## JOINT BACKER ROD



Non absorbent compressible grey closed cell polyethylene foam backup material. It is inserted into a joint to control sealant depth and create a backstop to allow proper sealant tooling. The Backer Rod is wound on a roll within the box.

Code	Colour	Size	Length Mtr	Each £
EBBROD13	GREY	13mm	750	59.00
EBBROD15	GREY	15mm	550	57.50
EBBROD20	GREY	20mm	350	56.95
EBBROD25	GREY	25mm	200	55.49
EBBROD30	GREY	30mm	160	54.95

## PRIMERS & CLEANERS




SILICONE PRIMER P1 for porous surfaces.  
SILICONE PRIMER NP 2 for non porous surfaces.  
SURFACE CLEANER for cleaning prior to application of all sealant types.

Code	Size	Each £
EBP1PRIM	1.25Ltr	19.95
EBP2PRIM	1.25Ltr	7.79
EBCLEA	1Ltr	7.89

# INDUSTRIAL SEALANTS/

## ADHESIVE/SEALANT - HYBRIFLEX 25

FROM  
£5.35



Highly flexible, low modulus (25 Shore A) neutral cure hybrid polymer based sealant. Isocyanate, silicone and halogen free, immediately overpaintable with most paints. Flexibility factor:  $\pm 50\%$ . It has excellent adhesion to most construction substrates, is resistant to most chemicals, non staining, temperature resistant from  $-40$  to  $+100^\circ\text{C}$ .

Conforms to ISO 11600-FG-25LM Used for general sealing in building industry, floor & wall joints with high movement requirements, window and door frame sealing and top glazing to timber and aluminium window frames.

Movement Accommodation	+/-20%	Skinning Time	15 mins
Elastic Recovery	80%	Elongation at Break	200%

Code	Colour	Size	Each £	Box Qty	Box £
EBFLEX25WH	WHITE	290ml	5.95	12	64.25
EBFLEX25GR	GREY	290ml	5.95	12	64.25

## ADHESIVE/SEALANT - PURAFLEX K11

FROM  
£4.46



PURAFLEX K11 is a premium quality low modulus polyurethane sealant designed to replace conventional one part polysulphide sealant in most applications. Permanently flexible to accommodate joint movement and adheres to most surfaces. Can be overpainted. Conforms to SNJF, ISO 11600 standards

Shore A	20-25	Movement Accommodation	+/-50%
Skinning Time	15 mins	Elastic Recovery	80%

Code	Colour	Size	Each £	Box Qty	Box £
EBFLEXK11WH	WHITE	C3	4.95	12	53.49
EBFLEXK11BL	BLACK	C3	4.95	12	53.49
EBFLEXK11GR	GREY	C3	4.95	12	53.49
EBFLEXK11BU	BUFF	C3	4.95	12	53.49
EBFLEXK11BR	BROWN	C3	4.95	12	53.49
EBFLEXK11WHF	WHITE	600ml FOIL	9.95	20	179.00
EBFLEXK11BLF	BLACK	600ml FOIL	9.95	20	179.00
EBFLEXK11GRF	GREY	600ml FOIL	9.95	20	179.00

## ADHESIVE/SEALANT - PURAFLEX 60

FROM  
£16.15



PURAFLEX 60 is a premium quality high modulus polyurethane adhesive (SA:60) and sealant that provides exceptional resistance to mechanical wear. Typically used for windshield or for high strength bonding. Has excellent chemical resistance. Conforms to SNJF, ISO 11600 standards.

Shore A	40	Movement Accommodation	+/-25%
Skinning Time	1-2 hrs	Elastic Recovery	70%

Code	Colour	Size	Each £	Box Qty	Box £
EBFLEXK60BL	BLACK	C3	17.95	12	193.85

## ADHESIVE/SEALANT - HYBRIFLEX 55

FROM  
£5.35



High strength, permanently elastic, neutral cure hybrid polymer based adhesive/sealant (55 Shore A). Isocyanate, silicone and halogen free, immediately overpaintable

with most paints. Flexibility factor:  $\pm 20\%$ . Hybriflex 55 has excellent adhesion to most construction substrates, is resistant to most chemicals, is non staining and temperature resistant from  $-40$  to  $+100^\circ\text{C}$ . Used for general bonding and sealing in industry, engineering, automotive, marine and O.E.M markets. Ideal metal to metal seam seal, provides excellent adhesion to most substrates. Also ideal for building industry uses as an adhesive and sealant in low movement applications.

Movement Accommodation	+/-20%	Skinning Time	15 mins
Elastic Recovery	80%	Elongation at Break	200%

Code	Colour	Size	Each £	Box Qty	Box £
EBFLEX55WH	WHITE	290ml	5.95	12	64.25
EBFLEX55GR	GREY	290ml	5.95	12	64.25
EBFLEX55BL	BLACK	290ml	5.95	12	64.25
EBFLEX55WHF	WHITE	600ml FOIL	9.95	12	119.40
EBFLEX55GRF	GREY	600ml FOIL	9.95	12	119.40
EBFLEX55BLF	BLACK	600ml FOIL	9.95	12	119.40

## TOP SELLER

### ADHESIVE/SEALANT - PURAFLEX 40

FROM  
£4.46



PURAFLEX 40 is a premium quality high modulus polyurethane sealant and adhesive that provides exceptional resistance to mechanical wear. Typically used in the caravan and marine industries and for sealing floor joints that are subject to high traffic. Has excellent chemical resistance, can be overpainted. Conforms to SNJF, ISO 11600 standards

Shore A	40	Movement Accommodation	+/-25%
Skinning Time	1-2 hrs	Elastic Recovery	70%

Code	Colour	Size	Each £	Box Qty	Box £
EBFLEXK40WH	WHITE	C3	4.95	12	53.49
EBFLEXK40BL	BLACK	C3	4.95	12	53.49
EBFLEXK40GR	GREY	C3	4.95	12	53.49
EBFLEXK40WHF	WHITE	600ml FOIL	9.95	20	179.00
EBFLEXK40BLF	BLACK	600ml FOIL	9.95	20	179.00
EBFLEXK40GRF	GREY	600ml FOIL	9.95	20	179.00

## SEALANT - CLEANER - AP3

FROM  
£11.50



SEALANT CLEANER AP3 is an all purpose organic solution of polysilanes. It may be used on glass or aluminium to improve the adhesion of PU or Hybrid Sealant on these substrates.

Code	Colour	Size	Each £	Box Qty	Box £
EBCLAP3	TRANSLUCENT	250ml	12.79	12	137.95

## SEALANT PRIMER- AP4

FROM  
£10.75



SEALANT PRIMER AP4 is an all purpose primer containing isocyanates. It may be used on different substrates (concrete, aluminium, wood, glass, plastic) to improve the adhesion of PU/hybrid sealants. Seals the porosity of materials such as wood or concrete, thus reducing or preventing problems of bubbling under severe conditions. May also be used as a barrier between sealant and paint to prevent the migration of plasticizers.

Code	Colour	Size	Each £	Box Qty	Box £
EBPRAP4	BLACK	30ml	11.95	12	128.99

## ADHESIVE - PURAFLEX PA

FROM  
£7.15



PURAFLEX PA is a premium quality high modulus polyurethane adhesive (SA:50) that provides exceptional resistance to mechanical wear. Typically used in the raised floor market to bond pedestals, also ideal for bonding brick slips and panels.

Shore A	50	Skinning Time	60 mins
Cure Time	4mm/24 hr	Tensile Strength	1.50N/mm <sup>2</sup>

Code	Colour	Size	Each £	Box Qty	Box £
EBFLEXPA	GREY	600ml FOIL	7.95	20	142.95

## SEALANT - HYBRIFLEX FL

FROM  
£9.95



Hybriflex FL has been formulated to provide a high shore A sealant combined with a low viscosity (easy flow) to enable high speed application into floor joints. Suitable for sealing saw cut and pre-formed expansion joints on both internal and external floor joints, provides exceptional abrasion resistance. The formula is also easy to apply at low temperatures.

Shore A	40	Movement Accommodation	+/-25%
Skinning Time	1-2 hrs	Elastic Recovery	70%

Code	Colour	Size	Each £	Box Qty	Box £
EBFLEXFOIL25	GREY	600ml FOIL	9.95	12	119.40

SEE ALSO »

Applicator Guns on  
Page 100